

DS-2CD864F-E(W) 1.3MP Network Box Camera




Specifications

DS-2CD864F-E(W)	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	Color: 0.01 lux@F1.2, AGC ON B/W: 0.001 lux@F1.2, AGC ON
Shutter time	1/25 (1/30)s ~ 1/100,000s
Lens mount	C/CS mount
Auto iris	DC drive
Day & night	IR cut filter with auto switch
Compression standard	
Video compression	H.264 / MPEG4 / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Audio compression	G.711 / G.726
Dual stream	Yes
Image	
Max. image resolution	1280 x 960
Frame rate	50 Hz: 25 fps (1280 × 960) 25 fps (1280 × 720) 60 Hz: 30 fps (1280 × 960) 30 fps (1280 × 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	
Network storage	NAS (iSCSI optional)
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
Security	User authentication, watermark
System compatibility	ONVIF, PSIA, CGI
Interface	
Audio input	1-ch 3.5 mm audio interface, MIC IN/LINE IN
Audio output	1-ch 3.5 mm audio interface (line level, 600 Ω)
Communication interface	1 RJ45 10M / 100M ethernet interface, 1 RS-485 interface
Alarm input	1
Alarm output	1
Video output	1 Vp-p composite output (75 Ω / BNC)
On-board storage	Built-in SD/SDHC slot, up to 32 GB
Reset button	Yes
General	
Operating conditions	-10°C ~ 60°C (14°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3af)
Power consumption	max. 5.5W (max. 8.5W with IR cut filter on) -W: max. 7W (max. 10W with IR cut filter on)
Dimensions	68 × 64.9 × 144.8 mm (2.7" × 2.2" × 5.7")
Weight	500g (1.1 lbs)

Key features

- Up to 1.3 megapixel (1280 x 960) high resolution
- Super low light
- H.264 / MPEG4 / MJPEG
- True day / night
- 3D digital noise reduction
- Wi-Fi optional

Dimensions



Available models

DS-2CD864F-E, DS-2CD864F-EW

* "-W": Wi-Fi (802.11g/b/n)

Accessories

