

CONTROL PANEL CR200



20-Zone PSTN Voice & Digital Communicating

A Modern, Effective and Versatile 20-zone Household Security System for the world's Monitoring System alarm market is heralded by our CR200.

It is packed with simple PLUG & PLAY functionality, with the design for easy installation and easily self-taught. Smart, sophisticated and safeguarded, CR 200 Plus certainly brings the most advanced Wireless Alarm System for you and your loved ones.

- PLUG & PLAY
- SELF-TAUGHT, SMART FEATURES
- TEXT ZONE NAMING
- FAULT-PROOF SUPERVISION

FEATURES

- A 20-zone full-feature Wireless Control Panel with built-in Voice & Digital dialers
- Total 6 numbers for Voice & Digital Reporting
- Communication protocol: Contact ID
- Voice messages can be recorded (max. of 20 sec) for voice reporting
- Remote arming & disarming via DTMF commands
- A 16 x 2 characters backlit full text LCD display
- Each of the 20 zones can be individually named/edited by the user for quick recognition of designated areas

- Built-in Transmitter to activate Outdoor Bell Box or Wireless Siren.
- "Home" arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm
- Full Supervision to ensure the problem-free operation of the system.
- Door Open Closed Monitoring before system arming adds extra caution.
- Fault Detection and Display
- Tamper detection protects the unit from unauthorized opening or removal from its mounting surface
- The Panel can interface with the following: RFID Tag Reader, Passive Infrared detector, Pet Immune Passive Infrared detector, Door Contact, Remote Keypad, Remote Controller, Wrist Emergency Transmitter, Optical Smoke Detector, Carbon Monoxide Detector, Water Sensor, Night Switch, Fixed Panic Button, External Bell Box, Wireless Siren, Universal Receiver and Repeater.

Specifications

Power : 9V 500mA adaptor

Back up battery: 7.2V 600 mAh Ni-mh rechargeable battery x 6

Battery back-up time: 8 hours minimum

Alarm output: 104dB @ 1M

Frequency available: 868.6375 MHz:

Range: Over 300 meters in open space

Operating temperature: -10° to +45°C

Humidity: up to 90% non-condensing

Dimensions: 185 X 120 X 26 mm

Complied with CE certification requirement

www.elkron.com - e-mail: info@elkron.it

