

CE

IR80B, IR80UL Passive infrared detector

Easytec

- 12 m wide-angle Fresnel lens
- Pet immunity up to 12 kg
- Intelligent signal evaluation
- Temperature compensation
- Choice of two application settings

Versatile in application. The ergonomic and discrete design, that fits to every environment, good pet immunity as well as progressive signal evaluation, the IR80 is ideal for the residential sector.

Safe and easy installation. The functional housing enables wall, 45° and corner mounting without accessories.


Outstanding immunity. The IR80 offers reliable catch performance with good immunity to environmental influences.


Safe detection. Thanks to the specially developed Fresnel lens high detection security is ensured. The signal evaluation guarantees good detection integrity by reliably differentiating between intruders and disturbance signals.

Coverage range and dimensions

Wide angle lens (standard)

Curtain mask (covering foil)





Technical data

9.0 16.0 VDC
2.0 VPP
Alarm at < 6.0 8.0 V
12 mA / 16 mA
30 Vpc / 100 mA / R _i 32 Ohm
2 3 s
LED
30 Vpc / 50 mA
0.3 3.0 m/s / 0.3 3.0 m/s
< 12 kg
-20 +55 °C
-20 +60 °C
<95 % r.h., non-condensing
>10 V/m
IP41 / IK02

Details for ordering

Туре	Part no	Designation	Weight
IR80B	A5Q00002067	Passive infrared detector (1 pc.)	0.100 kg
	562962.0-001	Passive infrared detector (250 pcs.)	25.000 kg
IR80UL	A5Q00001768	Passive infrared detector (1 pc.)	0.100 kg
	562289.0-001	Passive infrared detector (250 pcs.)	25.000 kg
IRUM2	519876.0-001	Swivel wall mount bracket	0.045 kg
IRUM3	519889.0-001	Swivel ceiling mount bracket	0.070 kg

Siemens Building Technologies AG Alte Landstr. 411 CH-8708 Männedorf Tel. +41 1 - 922 6111 Fax +41 1 - 922 6450 www.sibt.com

© 2003 Copyright by Siemens Building Technologies AG Data and design subject to change without notice. Supply subject to availability.