

OUTDOOR PROTECTIONS

MICROWAVE BARRIER

MWA Microwave barrier

MWA60R/T cod. MW5500111

Outdoor microwave barrier

- Range: 60m
- Nominal voltage: 12Vdc
- Min/max voltage: 11.5 - 15Vdc
- Absorption at rest: TX 31mA, RX 70mA
- Absorption in alarm condition: TX 31mA, RX 70mA
- Transmission frequency: 10.525 GHz (+/- 20MHz)
- Alarm relay block : signal on dedicated input
- Alarm relay: N.C. 500mA 12V
- Tampering protection : anti-opening switch (anti-disorientation kit available)
- Disqualification signalling: electrical output
- Modulation: 5 selectable channels
- Radiated power : 25 peak mW
- Operating temperature: -20 + 55 C° (heating kit available)
- Protection grade: IP 34
- Dimensioni (l x h x p): 176 x 230 x 133 mm.



MW60RT

MWA120R/T cod. MW5600111

Same as MW60RT but with range 120 m

MW30R/T microwave barrier

MW30RT cod. MW1900111

Outdoor microwave barrier

- Range: 180 m (program. 15 ÷ 100 m, 100 ÷ 180 m)
- Beam width: 6 m adjustable
- Four modulating channels
- Supply: 12 Vdc or 18 Vca
- Battery space: 12 Vdc - 1,9 Ah
- Frequency: in accordance with national frequencies
- Supply: 10,5 ÷ 14 Vdc, 16 ÷ 18 Vca
- Consumption: 85 mA (TX), 35 mA (RX)
- Beam width adjustments
- Automatic Gain Control (AGC)
- Intervention time adjustment
- Possibility of alternating current supply
- Anti-intruder tamper
- Setting and control test points
- Internal warning led for visualization during installation
- Dimensions (H x W x D) : 250 x 250 x 130 mm



MW30R/T

