


# High Security External Sounder & Strobe

Designed and engineered to provide maximum security in even the harshest of environments. The galvanised steel backplate and inner cover of the Odyssey 3 Metal combined with its additional outstanding features, ensure it is the complete external sounder solution.

## Outstanding features:

- 115db Volume
- Inner Cover, Lid & Wall Tamper
- 1.5mm Galvarnised Steel Enclosure
- Polycarbonate Cover & Lens
- IP65 Sealed Electronics
- Selectable SAB/SCB Mode
- Patented Safety Engineer Hold-off Mode
- Twin Alternating LEDs
- Advanced Microprocessor Technology
- Strobe Tube Saver

















#### Galvanised Steel Assembly

Shielding the IP65 electronics module and twin piezo sounders the 1.5mm galvanised steel backplate and inner cover assembly provides maximum protection against tamper without compromising aesthetics.



#### Patented Engineer Hold-off Mode

Installation and maintenance is made quick, simple and safe by a revolutionary patented safety engineer hold-off mode. On power-up the hold-off mode is automatically enabled, preventing the unit from sounding until the tamper circuit is secure. This enables "one trip up the ladder" installation Hold-off mode can be re-invoked at any time from the control panel, ensuring easy maintenance and verification.



#### IP65 Sealed Electronics Module

The advanced electronic module of the Odyssey 3 Metal is protected by a robust inner cover assembly with gasket seal. This maximises protection from dust and moisture, sealing to IP65 rating which enables prolonged exposure to harsher environments without compromising performance or functionality.



#### **Triple Tamper Detection**

Inner cover, lid and wall tamper detection is provided as standard. Wall tamper is derived from a fixing screw location, removing the need to drill additional fixing holes and providing optimum reliability.

### **Specifications**

Supply Voltage:	13.7V (nominal)
Current Drain	
Quiescent (inc charging):	15mA
Strobe:	100mA
Sounder:	425mA
Battery:	NiMh Stack, 7.2Vpc, 32omAh
Strobe:	1W, 1Hz Flash Rate
Dimensions:	315mm x 306mm x 78mm
Packed Weight:	3000g (106z) approx

#### **European Standards**

Safety: Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC).

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4: 1996. PD 6662 & EN 50131-1 Grade 3 Environmental Class IV.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texecom products are protected by UK and International patents, trademarks and registered design rights.

UK Registered Design Number 262365.

Odyssey is a trademark of Texecom Ltd. © 2009 (LIT-0035)





