

General Surveillance Management Centre



Introduction

DSS7016D is our first embedded general surveillance management centre integrating the software and hardware together. It adopts the self-development hardware platform and installs shining new DSS3.0 software. It fully enhances the system performance and has user-friendly GUI. It is easy to install, operate.

Features

Embedded device, 7*24 stable operation, client-server Architecture

High-performance stream media transfer and storage capability

Support distribute and cascade deployment

Support hot standby

Support local storage and IP-SAN storage

Support GIS map(Google, RasterMap)

Support ONVIF standard protocol connection

Support platform SDK

Front panel can displays system service status

Support POS function

Support People counting statistic

Support VDP, through SIP Server

Support Heat Map

Support fisheye calibration in playback.

Support GIS Map.

Support to set up the devices, such as IPC, NVR, MDVR and so on

Support Yahoo、Gmail、Hotmail

Performance

Support 2000 channels(Support 500 input devices)

Support 100 ONVIF Devices

Support 500 devices to auto-Register

Support unlimited accounts management and 8000 online users and max 500 roles

Support 700M transfer capability

Support 700M local storage capability

Support 20 distributes server and 5-level cascade

E-map max displays 200-channel on one screen

Process 1000-channel alarm per second.

DSS Client support 4K signal decoding

Support 500 VTO/VTH Devices

Support Max 300TB storage capability per storage server

Support max 200 access control devices

Specifications

Model	DSS7016D		DSS7016DR
System			
Main Processor	Intel Core I5 64 bits , 4 Core Processor		
Operating System	Embedded Linux		
Motherboard	Embedded Board(support 7*24 operation)		
Memory	8GB DDR3		
Case	Hot-dipped galvanized sheet steel (1.2mm thickened),High-precise aluminum alloy slide, Patented pull-out rack design.		
LocalSystem Setting	System time setting, Platform service operation parameters configuration		
Power Supply	Single Power Supply	Redundant power supply	
Display Port			
LCD	Display system information and status. Include: system time, the system hardware information, platform service running state, etc		
Data Management			
Hard Disk	One system disk and 15 disks local storage (max support 4T HDD)		
Raid mode	Single,Raid0, Raid1, Raid5, Raid6, Raid10		
Ethernet Port			
Ethernet Port	4 1000Mbps Ethernet port		
Features	Four Ethernet ports bound load balancing or independent Ethernet port interfaces		
Data Interface			
USB	4 USB2.0 port		
Serial Ports	1 RS232 COM		
Others			
HDD Hibernation	Main thoroughfare through the backplane		

Fault Alarm	Support for E-mail, beep, SDK, etc. For fault alarm
Power Supply	100V~240V,47~63Hz, Hot-swappable
Power	10W~200W(With HDD)
Work Temperature	0℃~50℃
Work Humidity	5%~90%(non-condensation)
Weight	20Kg
Dimension	526mm*485mm*135mm

Dahua Technology Co., Ltd.

1187BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.